

## NISOTEC 2T GARDEN

NISOTEC 2T GARDEN is a premium quality, synthetic based lubricant for 2-stroke engines. It provides safe lubrication and cleanliness for two stroke engine parts even in case of extreme climatic and operating conditions. It is formulated for excellent engine protection and cleanliness and reliable control against exhaust system blocking, and helps reduce exhaust smoke. NISOTEC 2T GARDEN is suitable both for all oil-injection and premix systems and meets the requirements of leading manufacturers. Especially recommended for high-speed air-cooled two-stroke garden equipment: rotary hoes, lawn-mowers, motor scythes, chain-saw engines and power generator engines. Should not be used in outboard engines. Performance Features and benefits:

- Very good engine protection and cleanliness
- Reliable control against exhaust system blocking
- Outstanding engine cleanliness
- Reduced exhaust smoke
- Very good self mixing with leaded and unleaded petrol

**Performance Levels:** NISOTEC 2T GARDEN satisfied and exceeds the requirements of all major OEM manufacturers and the international specifications.

SRPS ISO 6743-15, ISO 13738-2000, JASO-FD, ISO-L-EGD, API TC, GLOBAL GC, HUSQUARNA 272, STIHL

### Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Colour	-	Red	Visual
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	9.5	SRPS ISO 3104
Flash Point	°C	70	SRPS EN ISO 2719
Pour Point	°C	-27	SRPS ISO 3016
Sulphated ash	%	0,1	SRPS ISO 3987

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

### Packaging

<i>0.1L</i>	<i>0.25L</i>	<i>0.5L</i>	<i>1L</i>	<i>4L</i>	<i>10L</i>	<i>60L</i>	<i>180KG</i>	<i>850KG</i>	<i>IBC</i>	<i>AC</i>
	X20	X20			X2		X			