

NISOTEC TRAKTOL PREMIUM SAE 10W-30

NISOTEC TRAKTOL PREMIUM SAE 10W-30 is premium “universal tractor transmission oils” (UTTO) designed for use in transmissions, hydraulic systems, oil immersed brakes and other ancillary systems fitted to agricultural tractors and off-road equipment. NISOTEC TRAKTOL PREMIUM 10W-30 is a suitable for use in most modern equipment and tractors new generation, in which are functionally related hydraulics, transmissions and wet brakes, and the whole system is supplied with oil from the same common, or at most two cases. It can be used when SAE J306 80W and 85W grade is recommended. NISOTEC TRAKTOL PREMIUM 10W-30 have been evaluated against the latest requirements of leading tractor and transmission manufacturers including John Deere, Massey Ferguson, Ford-New Holland and GM Allison. Features and Benefits:

- Outstanding resistance to breakdown caused by oxidation and high temperatures
- Exceptional low temperature performance which allows easier cold weather start-up of all
- Minimising brake noise
- Controlled frictional properties - this helps prevent brake noise and brake chatter

Performance Levels: John Deere J20C/J20D, Ford M2C 134D, Ford M2C 86B, Massey Ferguson M1135/M1141/M1143/M1145, API GL-4, Allison C-4, Caterpillar TO-2, Kubota UDT, Case MS-1204, 1206, 1207, 1209, Case New Holand MAT 3525, Denison (Pump only) HF-(0 – 2), Sperry Vickers/Eaton: I-280-S

Characteristics

<i>Properties</i>	<i>Units</i>	<i>Typical Values</i>	<i>Methods</i>
Density at 15° C	kg/cm ³	0,87	SRPS EN ISO 3675
Kinematic viscosity at 100° C	mm ² /s	9	SRPS ISO 3104
Index viscosity	-	150	SRPS ISO 2909
Dynamic viscosity, CCS (Brookfield at -20° C)	mPa.s	3500	ASTM D 2983
Flash Point, COC	°C	215	SRPS EN ISO 2592
Pour Point	°C	-39	SRPS ISO 3016
Copper corosion , 3h, 100 ° C	ocena	1a	SRPS ISO 2160
Foaming, max. Seq. I / II / III	ml	20/0, 50/0, 20/0	SRPS ISO 6247

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

Packaging

0.1L	0.25L	0.5L	1L	4L	10L	60L	180KG	850KG	IBC	AC
				X4	X2		X			